

PART 1 - GENERAL

1.1 SUMMARY

- A. This Section includes the following:
 - 1. Vinyl composition tile (VCT).

1.2 PERFORMANCE REQUIREMENTS

- A. Static Coefficient of Friction: For tile installed on walkway surfaces, provide products with the following values as determined (both wet and dry conditions) by testing identical products per ASTM D 2047:
 - 1. Level Surfaces: Minimum 0.6.
 - 2. Step Treads: Minimum 0.6.
 - 3. Ramp Surfaces: Minimum 0.8.

1.3 PROJECT CONDITIONS

- A. Maintain temperatures within range recommended by manufacturer.
 - 1. 48 hours before installation.
 - 2. During installation.
 - 3. 48 hours after installation.

1.4 EXTRA MATERIALS

- A. Furnish extra materials described below that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 - 1. Floor Tile: Furnish 1 box for every 50 boxes or fraction thereof, of each type, color, and pattern of floor tile installed.

PART 2 - PRODUCTS

2.1 MATERIALS

- A. As required by Design/Builder and manufacturer to maintain warranty.

PART 3 - EXECUTION

3.1 GENERAL

- A. As required by Design/Builder and manufacturer to maintain warranty.
- B. Provide moisture test of floor substrate per manufacturer's recommendation prior to floor tile installation. Manufacturer to approve and accept floor conditions and moisture content prior to floor installation.

END OF SECTION